

Account Information

Date Client Name:

Vendor Name:

Phone Number Fax Number

Contact: Email Address:

Mobile Phone:

Ship To

Name

Address

Province Postal Code

Phone Number

Please complete this form and return to Permobil by fax OR click the button to send via email.

Please check appropriate boxes:

Trial fit Final finishing Desired width of system:

OBSS Back & Seat— Finishing Form

Order Form

Effective Date 04/12/2018

Before fabrication can begin, we must receive all 5 pages of this order form filled out completely and the digitized file.

Note: Please print client name clearly and correctly as you would like it to appear on the removable cover.

Notes:

Back – OBSS Finishing Form

Modification Options (please check appropriate boxes)

Overall Dimensions —please specify amount (and side if not equal)			
Increase	Decrease	Height from client top	cm/inch
Increase	Decrease	Height from client bottom	cm/inch
Increase	Decrease	Width from client right	cm/inch
Increase	Decrease	Width from client left	cm/inch

Rail Cuts	
Width from inside cane to inside cane: _____ cm/inch	<p>RD = Rail Depth RW = Rail Width</p>

Thin Laterals			
Left	Right	Both	None
Check selection			
Rail Cut:			
Width:		Depth:	

Steel Reinforcement (please check)					
Client left	Client right	Both	None	1/8" steel	Double reinforcement
(indicate positions and size on BACK)					
Belt notches/shoulder harness		Pass through belt guide		Soft spot	
Ventilation holes		Velcro		Round top corners	

BACK Mounting Hardware Section	
T-Nut (standard 1/4–20")	Quantity required:
T-Nut Placement Details	
T-Nut placement identified on cushion:	Yes No
If no, please be sure to provide details on preferred placement in the location of mounting hardware of this finishing form (next page).	
Spacing:	
Ottobock flat bracket (flush mount)	Ottobock slide brackets
Ottobock drop hooks: 1" 2" 3"	Other:

Supply Cover (specify number of covers in appropriate box)		
Eastex	Dartex (water resistant)	Spacetex
Neoprene	Reverse Dartex	Other (will supply material)

Spray Finish

BACK—Special Instructions

(clearly number instructions to correspond with numbers written directly on the BACK)

Empty space for special instructions.

Seat – OBSS Finishing Form

Modification Options (please check appropriate boxes)

Overall Dimensions —please specify amount (and side if not equal)			
Increase	Decrease	Width from client right	cm/inch
Increase	Decrease	Width from client left	cm/inch
Increase	Decrease	Depth from client front	cm/inch
Increase	Decrease	Depth from client back (posterior)	cm/inch

Seat Notches:	
Width from inside cane to inside cane:	cm/inch
Depth of seat notch:	cm/inch

RD = Rail Depth
RW = Rail Width

Thin Seat Adductors			
Left	Right	Both	None

Steel Reinforcement (please check)					
Client left	Client right	Both	None	1/8" steel	Double reinforcement
(indicate positions and size on SEAT)					
Belt notches/shoulder harness		Pass through belt guide		Waterfall front edge of seat	
Soft spot		Ventilation holes			
Velcro		Round corners			

Undercut Front Edge of Seat		Leg Length Discrepancy	
Add	cm/inch	Remove	cm/inch
		From client left	From client left
		Indicate locations on the SEAT	

SEAT Mounting Hardware Section:			
T-Nut (standard 1/4–20")	Quantity required:		
T-Nut Placement Details: T-Nut placement identified on cushion:	Yes	No	
If no, please be sure to provide details on preferred placement in the location of mounting hardware of this finishing form (next page).			
Spacing:			
Ottobock flat bracket (flush mount)			Ottobock slide brackets
Ottobock drop hooks	1"	2"	3"
None	Other (please specify):		

Supply Cover (specify number of covers in appropriate box)		
Eastex	Dartex (water resistant)	Spacetex
Neoprene	Reverse Dartex	Other (will supply material)

Spray Finish

SEAT – Special Instructions

(clearly number instructions to correspond with numbers written directly on the SEAT)

Empty space for special instructions.